



 **STAR LINK[®]**
Your needs.... Our Solutions !

Bio Face Reader

In House Designed & Developed

Introduction

The Bio face reader is robotically analyzing the facial expression like eyes, cheeks, ears and different facial elements via capture the photograph and match or maps it with the database. It has come upto 5 lakh transaction records. The system is capable of modeling a face in actual-time, with none manual initialization needed.

Face biometrics have the ability to be integrated anywhere you may discover a current digital camera. Law enforcement agencies the world over use biometric software to scan faces in cctv footage, as well as to identify person of interest in the field. Border control deployments use face recognition to confirm the identities of tourists. It even has client applications.



Features

High Resolution infrared Camera

IR LEDs for Night Vision

Enroll Upto 10,000 User

3D Image Sensing

High Speed Face Matching

Voice Guided Message

Upto 5 Lakh record capacity

Keypad : Touch, Alphanumeric

In-Built 4800 mAh

Backup up-to 2.5 hours



Specifications

Cortex A7 Dual Core, 1Ghz Processor

Display : 3.2" ,240×320 TFT color 262K

USB Port : Pen Drive for firmware upgrade and data transfer

Communication Method : Standard TCP / IP, USB Host

Operating Distance : 40 – 80 cm

Operating Temperature : 0 to 40 degree Celsius

Operating Humidity : 20 to 90% through Adapter

Power : Max 15 watt

Environment Light : 0-500 Lux

Visual indicator : Green / Red for Acceptance & Rejection.

Audio Indicators : Voice-Guided message (Adjustable volume)

Battery Backup : In-built battery 3.7V 4800 mAh backup up-to 2.5 hours depending on uses.

Keypad : Touch, Alphanumeric

Dimension / Weight : L:165mm H:165mm W:135mm Weight:1.3kg

Punch Size : 34 Byte

Face Recognition

Camera : High Resolution Infrared Camera / 3-D Image analysis

IR LEDs for Night Vision

Verification Speed : Less than 1 Second

Identification Time : 1 ~ 2 Second

Per Punch Size : 34 Byte

Recognition Algorithm : Feature extraction and pattern matching

Verification Method : Face recognition only.

Stored Template Size : 4KB Per User (12KB in case of 3 face enrollment)

Operational Mode

Face recognition only



Star Link Face reader is capable to work with



FLAP BARRIER



TRIPOD TURNSTILE



EXIT BUTTON



DOOR LOCK

Service & Support



STAR LINK - Member of ESAI

STAR LINK (ISO 9001 : 2015) has been registred in **ELECTRONIC SECURITY ASSOCIATION OF INDIA** under leading manufacture of Biometric Devicer



ELECTRONIC SECURITY
ASSOCIATION OF INDIA

ID - MA0280DL

For Any Biometric Needs

Contact :

Star Link Communication Pvt. Ltd.

D-88/4, Okhla Industrial Area Phase-I, Delhi - 110020

Toll Free No: 1800-11-8088

Email:sales@starlinkindia.com

Phone :+91-11-4059-8888 (100 Lines)



THANK YOU....

