

Complete Customized Solution For Attendance & Access Control



Bio Face Reader With *Thermal Temp. Screening*

- Thermal FAR infrared sensing
Spectrum: 9000-14000 nanometer
- Narrow point temperature sensing
- Temperature measurement range: 32-42 °C
- Ambient temperature range : 16 to 50 °C
- Measurement Resolution 0.1 ° accuracy : +/- 0.2 °C
- DSP data processing with FIR & IIR filter
- Person/date wise temperature report generation
- Aggregated report generation
- User Capacity - 10,000 templates
- Recording Capacity - 5 Lacs transaction
- High Resolution Infrared Camera
- Built in Battery (4800mAh)
- Upto 6 to 6.5 hours of battery backup
- Voice Guided Message in Hindi/English

FACE/ CARD READER

WWW.STARLINKINDIA.COM

BIO FACE READER-A PANACHE OF STYLE AND GRANDEUR

BIO - FACE READER

Processor	Cortex A7 Dual Core, 1Ghz
User Capacity	Enrol upto 10,000 users (One face enrollment)
Display	3.2", 240x320 TFT color 262K
Keypad	Touch, Alphanumeric
Dimension/ Weight	L:165mm H:165mm W:135mm / weight: 1.3kg
Camera	High resolution infrared camera (IR LEDs for night vision)
Recording Capacity	Max 1000 days or up to 5 lacs records
Recognition Algorithm	Feature extraction and pattern matching
Verification Method	Face recognition/ Proximity card
Verification Speed	Les than 1 second
Operating Distance	40 - 80cm
Operating Temperature	0 to 50°C
Operating Humidity	20 to 90% non-condensing
Power	Max.15 watt
Environment Light	0-500 Lux
Communication Method	Standard TCP /IP, USB Host
Installation Method	Wall Mounting
Template Size Storage	4KB Per User (12KB in case of 3 face enrollment)
Identification Time	1~2 Second
USB Port	Pen Drive for firmware upgrade and data transfer
Connectivity Port	RJ45 Port for Ethernet Connectivity
Visual Indicator	Green/Red for Acceptance & Rejection
Audio Indicator	Voice-Guided message (Adjustable volume)
Battery Backup	In-built battery 11.1V, 4800 mAh backup up-to 6 to 6.5 hours on Continues punching and stand by up 20 hours
Per Punch Size	34 byte

Authorized Distributor /Dealer:



SALES & SUPPORT ALSO AVAILABLE AT :

Ahmedabad, Alwar, Agra, Baddi, Bengaluru, Bhopal, Bhubaneswar, Chandigarh, Chennai, Dehradun, Faridabad, Gorakhpur, Gurugram, Guwahati, Haridwar, Hyderabad, Indore, Jaipur, Jalandhar, Jamshedpur, Jammu, Kanpur, Kochi, Kolkata, Ludhiana, Lucknow, Mumbai, Nasik, Nepal, Noida, Nagpur, New Delhi, Panaji, Pune, Raipur, Roorkee, Rudrapur, Solan, Surat, Thiruvananthapuram

Head Office :

D-88/4, Okhla Industrial Area
Phase-1, New Delhi - 110 020

STAR LINK COMMUNICATION PVT. LTD.

Ph.: 011- 4059 8888 (100 Lines), Fax: 011- 4052 6082
Email : sales@starlinkindia.com | www.starlinkindia.com

Manufacturing Unit:
Plot No.2/5, Mall Road,
Solan, H.P. - 173 212