M/s STARLINK COMMUNICATION PVT. LTD., An ISO certified manufacturer of highly versatile Access & Time Management systems with the brand name of "STARLINK". All requisite skills & capabilities for producing-Attendance, Access Control, Smart Card, RFID, Biometric Technology based system.

• Own Research & Software Development Team · Sales & Service available all over India.

CUSTOMIZED INSTALLATION DONE AT VARIOUS SECTORS

- · Government Sectors
- · Automobile Industry-Major Manufacturers and their allied Component Manufacturers
 - · Electronics, Computer & Telecom Industry
 - · Hotels, Catering Service Providers
 - · Airlines, Travel & Lagistic Services · Hospitals, Pharmaceuticals & Health Care
 - Products
 - · Steel, Foundry & Tool Industry
 - · Builders, Architects & Interiors
- · Educational Institutes, Consultants (Finance, Engineering, Legal, Security etc.)
 - · Sugar Mills Miscellaneous Units

SALES & SUPPORT NETWORK

NORTH ZONE: New Delhi, Gurgaon, Noida, Faridabad, Jaipur, Chandigarh, Ludhiana, Jalandhar, Jammu, Roorkee, Haridwar, Dehradun, Rudrapur, Lucknow, Kanpur, Solan,

SOUTH ZONE: Bangalore, Chennai, Hyderabad, Thiruvananthapuram, Kochi

EAST ZONE: Kolkata, Bhubneshwar, Guwahati, Gorakhpur, Patna, Jamshedpur

WEST ZONE: Mumbai, Nasik, Pune, Ahemadabad,

CENTRAL ZONE: Indore, Bhopal, Nagpur, Raipur

Authorised Distributor / Dealer





COMPLETE ATTENDANCE & **ACCESS CONTROL SOLUTIONS**

LARGEST MANUFACTURER OF **ATTENDANCE & ACCESS CONTROL READERS IN INDIA**

- In-house Design, Development & Manufacturing
- · Customization on demand
- . Cater to the needs from small offices & single location to Multiple Company, Multi Location & Multi Division
- · Guarantee after Sales Support
- · Over 3000 satisfied Customers across India

WORLD CLASS READERS MADE IN INDIA

- · Biometric/Card (RFID) based Attendance System
- · Access Control System
- · Leave Management System
- · Employee Management Payrall Solutions
- · Canteen Management System
- · Visitor Management System
- · GPRS/Wirless based Solutions
- · CCTV Security Surveillance
- Customized interfaces for HRMS/ERP/SAP
- · SDK Software development integrated kit.
- · Web Based online control
- · Push Technology for immediate reporting
- Web based/Window based/Online console applications available
- · User friendly GUI based Softwares

STAR LINK COMMUNICATION PVT. LTD.

Ph. 011-40598888 (100 Lines), Fax: 011-40526082 Works: Plot No.2/5, Mall Road, Solan, H.P. - 173212 Email: sales@starlinkindia.com

www.starlinkindia.com

t to those productive specific the major's producers are salest to major which you wise, 1990 by the against to ONE COMMUNICATION OF THE

www.starlinkindia.com

All Products are designed to meet Indian ambient conditions & work environments.

CLASSIC MODEL

- · Mifare Card / EM Card / Finger Print Reader
- LCD Display / 16 characters x 2 rows
- 32 bit RISC Micro Processor
- * 8 Digit alphanumeric card number
- · Recording capacity of 1,00,000 records
- 2,000 25,000 Finger template storage
- Red & Green Indicators,
- With built-in TCP/IP connectivity
- · USB Port (Optional at extra cost)

BIO STAR

- LCD 128 x 64 Graphics Display.
- 32bit RISC Micro Processor
- · 8 digits alphanumeric card number
- Recording capacity of "S Lacs" records
- 2,000 9,560 finger template storage
- Voice Guided message in Hindi /English (for Acceptance /
- Visual Indicator Red/ Green LED/Message on LCD
- · With built-in TCP/IP connectivity & USB port

BIO LINK

- LCD 128 x 64 Graphics Display
- 32bit RISC Micro Processor
- · 8 digits alphanumeric card number
- Recording capacity of "2 Lacs" records
- 600 finger template storage
- Voice Guided message in Hindi /English (for Acceptance / Rejection)
- Visual Indicator Red/ Green LED/Message on LCD
- With built-in TCP/IP connectivity & USB port

BIO LYNX

- LCD 128 x 64 Graphics Display
- 32bit RISC Micro Processor
- · 8 digits alphanumeric card number
- Recording capacity of "5 Lacs" records
- 2,000 9,560 finger template storage
- Voice Guided message in Hindi /English (for Acceptance / Rejection)
- Client / Server Mode, Time Synchronization
- External Color VGA Camera Interface (Optional at extra
- Communication Mode R\$232, USB, TCP/IP
- GPRS Data Card GSM & CDMA, SIM Connection (Optional at extra cost)
- WiFi (Optional at extra cost)

BIO TRACK

- · Touch Screen & Joy Stick
- TFT 3.2" 320×240 Graphics Display (48.20mm × 64.80mm)
- 2 GB SD Memory Card almost unlimited records Storage
- Communication Mode: RS232, USB, TCP/IP, GPRS
- · With inbuilt battery back-up upto 6 Hours
- 2,000 9,560 finger template storage
- Voice Guided message in English/Hindi (for Acceptance / Rejection)
- Client / Server Mode
- Inbuilt Color VGA Camera .
- Time Synchronization, Mailing
- WiFi (Optional at extra cost)





STAR LINK READERS















- Only Finger
- Only Card (Mifare/EM)
- · Card with Finger
- Card with Password
- Pin with Password
- Only PIN
- Note: Combination varies as per
- · All 10 finger can be enroll per Employee
- Scratch proof scanner
- ISO Finger Template Compatibility



INDUSTRIAL MODEL

- · Mifare Card / EM Card / Finger Print Reader
- Large LCD Display / 16 characters x 2 rows
- 32 bit RISC Micro Processor
- 8 digit alphanumeric card number
- Recording capacity of 1,00,000 records
- 2,000 25,000 Finger template storage
- Large Red & Green Indicators
- Heavy Duty Metallic Body
- With Built-in Battery backup upto 48 hrs
- With built-in TCP/IP connectivity

STRIAL MODEL WITH PRINTER

- Mifare Card / EM Card / Finger Print Reader
- Large LCD Display / 16 characters x 2 rows
- · 32 bit RISC Micro Processor
- · 8 digit alphanumeric card number
- Recording capacity of 1,00,000 records
- 2,000 25,000 Finger template storage
- Large Red & Green Indicators
- Heavy Duty Metallic Body
- With built-in Battery backup upto 48 hrs
- With built-in TCP/IP connectivity
- **Built-in Thermal Printer**

NDUSTRIAL BIO LYNX

- Large LCD 128 x 64 Graphics Display
- · 8 digits alphanumeric card number
- · Recording capacity of "5 Lacs" records
- 2,000 25,000 Finger template storage
- Voice Guided message in Hindi /English (for Acceptance /
- Client / Server Mode, Time Synchronization
- Communication Mode RS232, USB, TCP/IP, GPRS
- · Heavy Duty Metallic Body
- With Built-in Battery backup upto 48 hrs
- GPRS Data Card GSM & CDMA, SIM Connection (Optional at extra cost)
- · WiFi Optional (Optional at extra cost)
- Color VGA Camera (Optional at extra cost)

FACE READER

- Processor: TI DM CPU 600 Mhz
- LCD 3.5 inch TFT Color Screen
- User Capacity 500 Faces
- Specialized Double Sensor
- · Verification Method Only Face / Card with Face / Finger with Face
- · Recording capacity of "1.5 Lacs" records,
- Recognition Algorithm Dual Sensor ¹⁴ V2.0
- Built-in Battery Backup upto 5 hrs. (Optional at extra cost)
- Cover Height 1.40m 2.15m of individuals
- Communication Mode -TCP/IP, USB

DOOR CONTROLLER

- Processor 32 bit RISC Micro Controller
- 2 MB Flash with data storage of 62500 records
- No. of Doors Control 8 / 4
- No. of readers connected 15 / 8
- Dimension 21cm x 14 cm x 5 cm
- Piezo electric buzzer for accept / reject audio indication
- Lock to Controller distance: depend on wire resistance
- RS 485 networking range 800 meters
- Multiple Time zone to restrict access time wise
- EM / Mifare Slave Reader for Entry & Exit.